

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
22 February 2001 (22.02.2001)

PCT

(10) International Publication Number
WO 01/13081 A1

(51) International Patent Classification⁷: G01L 3/10, 1/12

(21) International Application Number: PCT/GB00/03119

(22) International Filing Date: 14 August 2000 (14.08.2000)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
9919065.4 12 August 1999 (12.08.1999) GB

(71) Applicant (for all designated States except US): FAST
TECHNOLOGY GMBH [DE/DE]; Otto-Hahn-Strasse
24, Gewerbegebiet Riemerling, D-85521 Ottobrunn (DE).

(72) Inventor; and

(75) Inventor/Applicant (for US only): MAY, Lutz, Axel
[DE/GB]; 3 The Grange, Newbury, Berkshire RG14 6RJ
(GB).

(74) Agent: BLUFF, John, William; Lloyd Wise, Tregear &
Co., Commonwealth House, 1-19 New Oxford Street, Lon-
don WC1A 1LW (GB).

(81) Designated States (national): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ,
DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR,
HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR,
LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ,
NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM,
TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian
patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European
patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE,
IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG,
CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published:

— With international search report.

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: MAGNETISED TRANSDUCER ELEMENT FOR TORQUE OR FORCE SENSOR



(57) Abstract: A magnetic transducer element for use in sensing torque in a contactless transducer system for rotating shaft (10) comprises an annular region (22) of magnetisation induced in the shaft (10) by rotating it about its axis (A-A) with respect to a magnetising source (50) oriented to create longitudinal magnetisation (Mf) in the annular region. The source may be a U-shaped (horseshoe) magnet with its poles axially spaced and with the gap (g) between the poles substantially greater than the axial width (w) of the poles. The application of torque to the shaft skews the longitudinal magnetisation to generate a torque-dependent tangential circumferential field component (Ms). This tangential field component is sensed by an external sensor or sensors (30a, 30b) adjacent but not in contact with the annular transducer region (22). A pair of transducer regions can be employed as well as guard or keeper regions (20, 24) to enhance and stabilise the transducer region (22).